

Combihammer TE 70-AVR



Applications

- Hammer drilling in concrete, masonry and natural stone from 12 - 150 mm diameter
- Drilling holes for heavy-duty anchors from 20 - 40 mm in diameter
- Breaching and demolition with pointed and flat chisels
- Hammer drilling in concrete, masonry and natural stone with drill bits from 1/2" - 6" in diameter
- Drilling holes for heavy-duty anchors 3/4" - 1 3/4" in diameter

Advantages

- High speed of rotation (360 rpm) for extra drilling performance
- Optimized mechanical clutch for maximum torque transfer
- Maximum user comfort thanks to low contact pressure and Active Vibration Reduction (AVR) system for low vibration
- Center of gravity close to the grip for optimum balance
- Glass-fiber reinforced casing parts for ruggedness and long life

Technical data

Rated power	1800 W
Optimum drilling diameter in concrete	22 - 40 mm
Drilling diameter range for hammer drill bits	16 - 40 mm
Single impact energy	11.5 J
Full hammering frequency	2760 impacts/minute
Dimensions (LxWxH)	540 x 125 x 305 mm
Weight according to EPTA Procedure 01/2003	8.3 kg
Rotation speed gear 1 under no load	360 rpm
Service indicator	Yes



Ordering designation	Description	Sales pack quantity	Item number
TE 70-AVR 230V	1x Combihammer TE 70-AVR 230V, 1x Case	1	2062998