

puzzi 100

1.100-105

puzzi 200

1.193-105



ENGLISH

Page 2, 3–7, 21, 22

FRANÇAIS

Page 2, 8–12, 21, 22

ESPAÑOL

Página 2, 13–19, 21, 22



5.959-016 (10/00)

English

Care and Maintenance

Caution:

Before any maintenance work takes place, pull the power plug out of the socket.

- Check mains cable, connection cable and hoses for damage before putting the unit into operation for the first time.
- Before longer periods of disuse, the entire water must be drained out of the unit otherwise unpleasant odours might ensue.
- From time to time clean the suction strainer in the fresh-water tank and the fluff strainer (Fig. 11).
- No part has to be lubricated.
- Store the cord and the whole appliance in a dry area. Never store the cord in the water tanks of this appliance!
- Do not run over, crush or pull the power supply cable or extension lead, otherwise it may be damaged. Protect the cable from heat, oil and sharp edges.

Troubleshooting

Caution:

Danger from electrical current. Pull out mains power plug before any work is carried out on electrical parts.

No water coming out at the nozzle

1. Fresh-water tank empty, fill it.
2. Nozzle blocked, clean it.
3. Suction filter in fresh water tank blocked, clean it.
4. Spray pump defective, have it replaced by a technical expert.

Spray emitted from one side only

1. Nozzle is partly blocked, clean it.

Insufficient suction power

1. Cover not on properly, put it on properly
2. Seal on cover dirty, clean it.
3. Fluff strainer dirty, clean it.
4. Suction hose is blocked, check and clean it.

Spray pump too loud

1. Fresh-water tank empty, fill it
Have all inspections and work carried out on electrical parts done by a technical expert. For more extensive tasks contact customer service.

Technical data

Voltage variants

115 V (1~50/60 Hz)

Power, blower motor

Suction turbine P _{max}	1250	W
Suction turbine P _{nominal}	1100	W
Air flow, max	54	l/sec.
Vacuum	220	mbar

Power, spray pump

Spray pump	40	W
Spray pressure, max.	1	bar
Spray quantity	1	l/min.

Dimensions

Filling capacity, fresh water	10	l
Capacity, dirty water	9	l
Length	665	mm
Width	320	mm
Height	435	mm
Weight	10,3	kg

Sound level

Conforms to DIN 45635	68	dB(A)
-----------------------	----	-------

Safety class

II

Mains cable

Length	7,5	m
Type	H 05 VV – F 2x1	

Specifications subject to change without prior notice.