

Breaker TE 800-AVR



Drilling and Demolition

Applications

- Demolition work on walls
- Corrective work on floor slabs
- Breaking out openings for doors and windows
- Making penetrations for ducts and pipes

Advantages

- Powerful breaking performance thanks to exceptional impact energy and innovative Hilti chisels
- “D-handle” design for perfect balance in wall applications and good handling in universal use
- Lowest vibration values in its class thanks to Hilti’s innovative Active Vibration Reduction (AVR) sub-chassis system
- Hilti wall chisels developed exclusively for wall applications boost productivity and improve handling thanks to light weight, perfect length and air-hardened steel for outstanding tip sharpness
- Optional TE DRS-B dust removal system eliminates up to 95% of the fine dust produced
- One-touch power reduction button for use on lighter materials and for greater precision in controlled breaking jobs

Technical data

Single impact energy	21 J
Triaxial vibration for chiselling in concrete¹⁾	9.0 m/s ²
Weight according to EPTA Procedure 01/2003	10.6 kg
Active Vibration Reduction	Yes
Brushless motor	No
Full hammering frequency	1890 impacts/minute
Reduced impact energy	Yes
Dust removal module	TE DRS-B (optional)
Max. chiselling performance	2500 cm ³ /min
Constant speed motor electronics	Yes

¹⁾ according to EN 60745-2-6



Ordering designation	Package contents	Sales pack quantity	Item number
TE 800-AVR Combo A	1pc TE 800-AVR + 2pcs TE-SP SM36~Wave	1 pc	3540688
TE 800-AVR Combo B	1pc TE 800-AVR + 2pcs TE-SP SM50~Wave	1 pc	3540689
TE 800-AVR Combo C	1pc TE 800-AVR + 1pc TE-SP SM36~Wave + 1pc TE-SP SM50~Wave	1 pc	3540690
TE 800-AVR	1x Breaker TE 800-AVR 30V, 1x Case, 1x instruction manual, 1x Hilti grease, 1x cleaning cloth	1 pc	2064657